

Kare Sürücülü Hidrolik Tork Anahtarları

Square Drive Hydraulic Torque Wrenches



- » $\pm 3\%$ hassasiyetle torklama işlemi.
- » 72.000 N.m'ye kadar kapasite seçeneği.
- » Alüminyum-titanyum alaşımli yekpare, hafif gövde.
- » Sıkma ve sökme işlemleri için uygun tasarım.
- » Tek düğme ile değiştirilebilir kare sürücü adaptörü.
- » $360^\circ \times 180^\circ$ çok pozisyonlu dönebilmir yağ giriş portu.
- » Gövdeye işlenmiş, basınç-tork ayar tablosu.
- » Güvenlik kilitli, her yöne ayarlanabilir destek ayağı.
- » Türkiye'de servis ve kalibrasyon desteği.

- » $\pm 3\%$ high precision torque operation.
- » Available from 110 to 72.000 N.m.
- » Aluminum-titanium alloy lightweight, unibody.
- » Suitable for tightening and loosening process.
- » One-button exchangeable square drive adapter.
- » $360^\circ \times 180^\circ$ rotatable multi-position oil inlet port.
- » Laser engraved torque table on body.
- » Safety lock, adjustable reaction arm in all directions.
- » Repair, maintenance and calibration services.

Parça Part	Tork Gücü (N.m) Torque Range		Sürücü Sq. Drive	Ağırlık Weight	Ölçüler (mm) Dimensions									
	Min.	Max.	inç	kg	L1	L2	L3	H1	H2	H3	H4	R1	R2	R3
07 IBT	110	1.100	3/4"	1.8	110.8	139.3	46	42	65.8	76.2	108.1	20.5	68.3	54
1 IBT	180	1.800	3/4" , 1"	2.5	144.5	173.5	55	50	72	96	131	26	85	66.5
3 IBT	450	4.500	1"	5	178	229	75	68	95	127	176.5	34	114	89.5
5 IBT	750	7.500	1.1/2"	8	210.5	270.5	87	80	123	149	199	39	137	100
8 IBT	1.000	10.700	1.1/2"	11	222	293	88	90	134	167	217	47	153	120
10 IBT	1.550	15.500	1.1/2"	15	245.5	317.5	105	100	142	182	232	51	154	128
20 IBT	2.600	26.600	2.1/2"	26.5	307.5	383.5	127	120	183	220	270	59	186	153
25 IBT	3.400	34.700	2.1/2"	35	323	401	130	137	200	247	297	66	199	159.3
35 IBT	4.800	48.700	2.1/2"	50	372.5	496.5	135	153	216	282	332	77	241	167
50 IBT	7.200	72.000	2.1/2"	87	400	516	160	160	223	291	341	81	259	178

